# RF320I4B-N

## Universal transmitter Brown RF433 MHz

Each RF receiver monitors the alarm, battery, tamper and supervisory status of each transmitter.  In addition it reports any change in status to the panel, which takes action according to the programmed zone types.



## Details

- Learn-Mode Technology
- More than 3 years battery life
- 2 internal reed switches allow for vertical or horizontal mounting
- Wall and cover tamper
- Jumper to select one of the 2 reed switcher or the supervised external input

# RF320I4B-N

## Universal transmitter Brown RF433 MHz

## Technical specifications

### General

| | |
|---|---|
| Application type | Montagem em superfície |

### Wired/wireless

| | |
|---|---|
| Wired-wireless | Trådløs |
| Wireless frequency | Legado de 433 MHz |
| Open-air range | 150 m |
| Operating gap | 10 mm max. |

### Electrical

| | |
|---|---|
| Batteries | 1 x 3,6V Lithium |
| Battery lifetime | 3 a 5 anos |

### Physical

| | |
|---|---|
| Dimensions contact / sensor | 32 x 32 x 102 mm |
| Net weight | 44 g |
| Colour | Brun |

### Environmental

| | |
|---|---|
| Operating temperature | -34° to +60° C |
| Relative humidity | 0 to 90% noncondensing |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 28 May 2026 - 16:42