# DM2080I-N

**2000 Series Addressable MCP w/ Isolator - RED**



# DM2080I-N

## 2000 Series Addressable MCP w/ Isolator - RED

## Specyfikacja techniczna

### General

| | |
|---|---|
| Addressing method | DIP Switches |

### Electrical

| | |
|---|---|
| Power supply type | Loop-drevet |

### Detection

| | |
|---|---|
| Monitoring | Device type, Presence |

### Isolation

| | |
|---|---|
| Type | Negative line break |

### Physical

| | |
|---|---|
| Colour | Rød (RAL 3001) |
| Mounting type | Vægmontering |
| Material (body) | RA6 + 30%gF |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Environment | Indendør |

### Regulatory

| | |
|---|---|
| Compliancy | CE, REACH, RoHS 2, WEEE |
| Certification | CPR |

### Wyroby zgodne

| Kategoria | Odniesienie | Opis |
|---|---|---|
| Detection device | DM966 | Wymienne przezroczyste szybki do ręcznych ostrzegaczy pożarowych |

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57