ATS1181M

Sicherer MIFARE DESFire EV1/EV2/EV3-Kartenleser, Bluetooth, mit PIN, Ausgang und RTE-Eingang in schlankem Design, vorbereitet für mobile Lösungen mit Smartphone

Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Axon and Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Axon or Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

Communication

The reader communicates in a secure way over the ATS LAN databus to Axon or Advisor control panels using AES encryption, securing the data from the card until being processed.

Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.



Einzelheiten

- Secure ATS MIFARE DESFire EV1/EV2/EV3-Leser mit PIN-Tastatur
- Vorbereitet für mobile Authentifizierung über Bluetooth
- Unterstützt Secure Mifare (Secure Modus) oder Mifare 4 oder 7 Byte CSN/UID (Unsecure Modus)
- Verwenden Sie Secure Karten der Serie ATS145x oder Kundenkarten.
- Secure Kommunikation zwischen Leser und Everon / Axon / Advisor Advanced / CDC4-Bedienfeld mittels AES-128-Bit-Verschlüsselung
- Robustes Kunststoffgehäuse in schmaler Ausführung
- Montage im Innen- oder Außenbereich
- ATS-Bus-Schnittstelle
- Request To Exit - Eingang
- Open-Collector-Ausgang (Tür offen)
- Unterstützt ab Advisor Advanced MR4.8 und Axon MR1.0

ATS1181M

Sicherer MIFARE DESFire EV1/EV2/EV3-Kartenleser, Bluetooth, mit PIN, Ausgang und RTE-Eingang in schlankem Design, vorbereitet für mobile Lösungen mit Smartphone

Technische Spezifikationen

System

Reading distance	Secure: max. 2 cm Unsecure: max. 5 cm Bluetooth-abhängiges Mobilgerät und Einstellungen
Max. reader distance to panel	1500 m
CSN (Card Serial Number)	Yes
Custom data model	Yes
Supported card types	MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Card Addressing
No. of LEDs	3

Technology

Reader type	Smart Card
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (custom data), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data)
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Bytes (non-unique), 4 Bytes (S50), 7 Bytes (S50), 7 Bytes (S70)

Interface & connections

Interface	ATS RS-485
Connector type	Pigtail
Pigtail length	2 m

Inputs/outputs

Inputs	Request to exit
Outputs	1 Open Collector (10 mA)

Tamper type

Pry-off tamper	Yes

Operation

Stand-alone	No
PIN keypad	Yes
PIN length	Durch die Zentrale definiert

Electrical

Operating voltage	10,8 bis 30 VDC
Current consumption	55 mA bei 13,8 VDC normal 85 mA bei maximal 13,8 VDC

Physical

Physical dimensions	140 x 44 x 20 mm
Net weight	240 g
Shipping weight	275 g
Colour	Black
Material	Plastic
Form factor	Slimline
Mounting Type	Surface mount

Environmental

Operating temperature	-40 bis +55 °C
Storage temperature	-40 bis +55 °C
Relative humidity	<95 %, nicht kondensierend
Environment	Indoor, Outdoor
IP rating	IP67 IK09

Regulatory

Compliancy	CE



Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.