TVN-1204CS-000

TruVision NVR 12, 4 Kanäle, 4-Kanal PoE, 40 Mbit/s, ohne HDD



Einzelheiten

- Linux-basierte Plug-and-Play-Konfiguration
- Unterstützt H.264-, H.265- und H.265+-Codierung, abhängig von den Kameras.
- Vier Plug & Play PoE-Anschlüsse (PoE-af- und PoE-at-Unterstützung) mit einer maximalen Auflösung von 4K (8 MP)
- Automatische Einrichtung von IP-Adressen über Plug&Play-PoE-Ports
- Bis zu 40 Mbit/s Kameraaufzeichnungsbandbreite für maximal vier IP-Kameras
- Echtzeitaufnahme (bis zu 4 MP)
- HDMI/VGA-Monitorausgang
- TruVision IP-Kamera-Automatikerkennung
- Import/Export der IP-Kamerakonfiguration
- UltraSync-Unterstützung für Fernzugriff ohne Portweiterleitung
- Bewegungserkennung und VCA-Unterstützung, abhängig von den Kameras
- Spezielle Personen-/Fahrzeugerkennung in Kombination mit unterstützten Kameras
- Unterstützung von Kameras von Drittanbietern über ONVIF Profile S oder RTSP (benutzerdefinierte Protokolle)
- Integration von Aritech IP-Einbruchmeldeanlagen über SIA/XSIA-Berichte
- TVK-600 IP-Tastatur
- USB-DVD-Brenner-Unterstützung
- Vollständiger Zugriff über Browser, OSD und Software für Live- und aufgezeichnete Videos sowie Konfigurationen
- TVRMobile-App für iOS und Android zur Fernanzeige
- TruVision Navigator Client-/Host- oder Standalone-

Anwendungsunterstützung

- Externe Integration über SDK

Reasons to choose TVN 12

The TVN 12cS recorder series offers a full-featured, compact recording solution for IP cameras with a maximum resolution of 8 MP(4K).
The TVN-1204cS is a cost-effective, easy-to-use recorder capable of recording up to four IP cameras, connected to the built-in PoE ports or via the LAN network.

Easy to use

A setup wizard with auto detection of IP cameras guarantees a fast installation of the recorder.
The TVN 12cS can be added to the internet without port forwarding or VPN, thanks to the built-in UltraSync connectivity. Showing remote video on mobile applications was never easier.
In combination with dedicated TruVision cameras that can support people and/or vehicle detection, the TVN 12 recorder series can find relevant events faster and without efforts.

Applications

The TVN 12cS is the ideal recording solution for small commercial and residential applications, where ease of use and fast deployment time are important.

TVN-1204CS-000

TruVision NVR 12, 4 Kanäle, 4-Kanal PoE, 40 Mbit/s, ohne HDD

Technische Spezifikationen

General

Technology	IP
Operating system	Embedded Linux
Rack mountable	No

Video/audio input

Camera channels	4
IP camera channels	4
Camera bandwidth	40 Mbps
Audio compression	G.711alaw, G.711ulaw, G.722, G.726
Max. IP audio in	4
Max. analog audio In	1
Supported video compression standards	H.264, H.265, H.265+
Supported video streaming standards	Onvif, RTSP Custom Protocols

Local viewing

HDMI output	1
HDMI version	1.4, 2.0
VGA output	1
Max. local output resolution	4K
Synchronous playback OSD (channels)	Bis zu 4 Kanäle (1080p)

Remote viewing

Total available viewing bandwidth	80 Mbps
Max. live viewing streams	128 Streams
Max. playback viewing streams	8 Streams
Max. simultaneous playback web browser	Bis zu 8 Kanäle
Reverse playback web browser (channels)	Bis zu 8 Kanäle
UltraSync support	Yes, embedded
Software compatibility	Advisor Management Software (ATS8600), TruVision Navigator, TVRmobile
Browser compatibility	Google Chrome, Internet Explorer, Mozilla Firefox, Safari

Storage

SATA interfaces	1
Max. capacity per SATA HDD (TB)	8
Maximum recording resolution	4 K
Recording modes	Continuous, Event, Manual
External storage	NAS
Edge failover recording	Yes

Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100 Mbps self-adaptive Ethernet interface
PoE ports	4
Total PoE budget	50 W
PoE standards supported	PoE-af, PoE-at
Max. PoE budget per port	≤ 30 W
Plug & Play PoE support	Yes
Flexible PoE allocation	Yes
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	Yes

External interfaces

USB interface back	1
USB interface front	1
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

Electrical

Operating voltage	48 VDC
Power supply type	48 VDC
Power consumption without HDD (W)	≤65 W

Physical

Physical dimensions	320 x 240 x 48 mm (B x T x H)
Net weight	1,2 kg
Colour	Black

Environmental

Operating temperature	-10 bis +55°C
Relative humidity	10 bis 90% nicht kondensierend

Regulatory

Compliancy	CE, FCC, RCM, REACH, RoHS, UKCA, UL, WEEE

Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.