ACT455

25-pack PVC card, empty EV2

Product overview

The ISO card in white color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV1 or EV2 encryption. The card offers a 2 kB application memory. It can be used in secure mode with ATS118x range readers and ATS1136 keypad. It can also provide for Mifare 7-byte CSN.

Secure programming

Using the secure programmer with the Advisor Management cards and keyfobs can easily be programmed for secure use.



Details

- ISO card model
- Card data can be secured by Mifare Desfire EV1 or EV2
- Mifare Desfire EV2 card with 2 kB application memory
- Printed serial number
- Can be programmed with Secure Programmer

ACT455

25-pack PVC card, empty EV2

Technical specifications

System

Reading distance	Secure mode: between 1 to 5 cm Unsecure mode: between 2 to 5 cm Distance may vary based on reader
Custom data model	No
Memory size	2K
Supported readers	ATS ATS118x Secure Readers

Technology

Credential type	Smart kort
Credential operating frequency	13.56 MHz
Supported technology 13.56 MHz	Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (données personnalisées)

Printing

Direct surface printing	No

Ordering information

Minimum order quantity	1
Cards/tags in package	25

Physical

Material	PVC
Form factor	CR80 (Crédit)
Physical dimensions	86 x 54 x 9 mm
Net weight	66 g
Shipping weight	67 g
Colour	Hvid
Card Label	Serial number

Environmental

Operating temperature	-10 to +50°C
IP rating	IP68

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:23