ATS1140S42

***** INTERNAL PURPOSE, ONLY FOR FRANCE *** Everon - ATS1140-**

ATS1140S42

*** INTERNAL PURPOSE, ONLY FOR FRANCE *** Everon - ATS1140-

Technical specifications

General

User interface	Touch Responsive Surface Keys
Product line	Advisor Advanced, Everon
Status LEDs	1
Integrated reader	Secure MIFARE

System

Function keys	3
Supported card types	MIFARE® Classic UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Software Addressing
Supported cable type	WCAT 52/54 or equivalent

Communication

Communication type	Wired
Reading distance	Up to 3 cm

Inputs/Outputs

Inputs	1
Input type	Request to Exit (NO)
Outputs	1
Output type	Open collector (OC), 100 mA max, 15 VDC max.

Electrical

Operating voltage	12.0 to 13.5 VDC (provided by panel)
Current consumption	330 mA at 13.7 VDC, 375 mA at 12 VDC (max.) 220 mA at 13.7 VDC, 250 mA at 12 VDC (average) 70 mA at 13.7 VDC, 80 mA at 12 VDC (standby)

Physical

Physical dimensions	127 x 179 x 20 mm
Net weight	460 g
Colour	White
Mounting type	Wall mount
Material	ABS plastic

Environmental

Operating temperature	0 to +50°C
Relative humidity	up to 95% noncondensing
Environment	Indoor
IP rating	IP30 IK06

Regulatory

Certification	EN50131 Grade 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Compatible products

Category	Reference	Description
Control Panel	ATS1700-MM	Always On. Always Aware. Everon 1700 security panel, IP-onboard, EN grade 3, WebApp, 8 onboard zones max 48 zones, 4 areas, medium metal housing
Control Panel	ATS3700-MM	Always On. Always Aware. Everon 3700 security panel, IP-onboard, EN grade 3, WebApp, 16 onboard zones max 256 zones, 16 areas, medium metal housing
Control Panel	ATS4700-LM	Always On. Always Aware. Everon 4700 security panel, IP-onboard, EN grade 3, WebApp, 16 onboard zones max 1000 zones, 64 areas, Larger metal housing
Control Panel	ATS4700-MM	Always On. Always Aware. Everon 4700 security panel, IP-onboard, EN grade 3, WebApp, 16 onboard zones max 1000 zones, 64 areas, medium metal housing

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 11 June 2026 - 17:56