FF766N

16519 Triple IR Flame Detector In Eexd - IIC T6 Flame Proof Housing

General

The FF766N is a IR³ flame detector in a flame proof housing. IR³ models have excellent response to flame while providing superb immunity to extraneous sources. New micro-processor technology makes the detectors independent of flame intensity enabling it to operate through smoke, a layer of oil, dust, or water vapor. A high and low sensitivity setting according to EN54-10 is provided.

Successor of FF766

Installer and maintenance friendly

The units can be wired as conventional 2 wire, 4-20 mA, or relay contacts (fire, fault and pre alarm) in latching or non-latching operation. Remote test inputs are available to activate self-test.

A stainless steel adjustable bracket and weather shield is also available.

The units are tolerant to vibration, and wind does not affect the performance. The IR³ unit has excellent tolerance to detector window contamination and can detect flame through glass windows.

A flame sensor test unit is available for accurate testing of the detectors.

Reducing false alarms

Most IR flame sensors respond to 4.3µm light, emitted by hydrocarbon flames. By responding to 0.75 to 2.7µm light emitted by every fire, all flickering flames can be detected. Gas fires not visible to the naked eye e.g. hydrogen may also be detected.

The IR³ detectors, responding to adjacent IR wavelengths, enable it to discriminate between flames and spurious sources of IR radiation.

The combination of filters and signal processing allows the sensor to be used without risk of false alarms in difficult situations characterised by factors such as flickering sunlight.



Details

- Triple IR detector
- High specification units for critical applications
- IP66 Housing
- Flame proof housing
- Low current consumption
- 2 Wire, 4 - 20 mA and relay operation
- Latching and non latching operation
- High / Low sensitivity setting
- Tolerance to detector window contamination
- Remote self test facility
- Microprocessor controlled
- Immunity to false sources (arc welding, lightning and static)
- EN54-10 & CPD approved

FF766N

16519 Triple IR Flame Detector In Eexd - IIC T6 Flame Proof Housing

Technical specifications

Electrical

Operating voltage	14 to 30 VDC

Physical

Physical dimensions	146 x 150 x 137 mm (W x H x D)
Net weight	2.5 kg

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-20 to +65°C
Relative humidity	95% max. noncondensing
Environment	Exd, Indoor
IP rating	IP66

Supply voltage

	14 - 30 VDC

Supply current

	3/9, 4/8/14, 4-20, 8-20 mA

Relay contact ratings

	1 A @ 30 VDC (resistive load)

Field of view

	90° min. cone

Spectral response (IR)

	0.75 to 2.7 µm

Operating temperature

	-10°C to 55°C

Storage temperature

	-20°C to 65°C

Relative humidity

	95% non-condensing

IP Rating

	IP66

Weight

	2.5 kg

Dimensions

W x H x D	146 x 150 x 137 mm

IEC marking

	EEx d IIC T6

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 6 December 2024 - 9:01