VV602S3PLUS

Seismic detector for ATMs and night safe deposit boxes, NFA2P



VV602S3PLUS

Seismic detector for ATMs and night safe deposit boxes, NFA2P

Technische specificaties

General

Application type	ATM, Night safe deposit boxes
Tamper protection	Temperature 84°C, drill shield, opening contact, pry-off contact
Alarm indication	LED-indication screw no. 3
Low voltage alarm	7.5 V

Detection

Range	3 to 14 m radius
Sensitivity adjustment	5 steps of approx. 6 dB each

Inputs/outputs

Alarm contact	Form A solid state relay, max series resistance 35 ohm
Test output	Yes

Electrical

Power supply value	9 to 15 VDC
Current consumption	8.6 mA

Physical

Physical dimensions	81 × 101 × 28 mm
Net weight	380 g
Colour	Grey (RAL 7035)

Environmental

Operating temperature	-20 to +55°C
Relative humidity	90%
IP rating	IP30

Regulatory

Certification	NFA2P

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57