TX-2810-03-4

Wireless Outdoor PIR 868AM Gen2



Details

- Electronic range setting: 10/20/30m
- Attractive aesthetics
- 10 to 70° detection angle
- 180° pan & 90° tilt for flexible install
- Sensor module is hidden
- High dust and humidity resistance (IP65)

TX-2810-03-4

Wireless Outdoor PIR 868AM Gen2

Technische specificaties

General

Technology	PIR
Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No
Pry-off tamper kit	On board

Detection

Max. detection range	30 m
Detection range	30 m
Detection range selection	10, 20 or 30 m
Coverage (field of view)	70°
Undercrawl protection	No

Wired/wireless

Wired-wireless	Wireless
Wireless frequency	433 MHz legacy

Electrical

Batteries	CR123
Battery lifetime	3 years

Physical

Physical dimensions	125 × 175 × 130 mm
Net weight	334 g
Shipping weight	555 g
Colour	Silver
Material	High impact ABS plastic with HDPE cover, UV stabilized
Mounting height	3 to 6 m

Environmental

Operating temperature	-25 to +65°C
Environment	Outdoor

Regulatory

Compliancy	CE

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57