6931P

Zewnętrzny czujnik ruchu, Dual Technology, 24 GHz

Dual Technology outdoor motion sensor

The Mini Dual variants are outdoor motion sensors and alarm triggers that use two independent passive infrared detectors plus a microwave sensor module. All three sensors must trigger to cause the detector to signal an alarm. They use triple detection technology to deliver precise, reliable presence detection.

Easy and quick to install

Programmable options include a variable pulse count and LED able/disable functionality. Moreover, the integral dual-axis tilt sensor allows 90º of pan and 45º of tilt, which increases the speed of the outdoor installation and provides incredibly accurate aiming of the detection pattern.

Aesthetics and hidden sensor module

The design has a neat appearance that gives no visible indication of the orientation of the detector head and totally hides the wiring. It blends smoothly into residential outdoor applications.



Szczegóły

- Nowa rodzina urządzeń zewnętrznych zawierająca przewodowy czujnik PIR, 2 warianty Dual Technology i bezprzewodowy czujnik PIR
- Atrakcyjna obudowa
- Kąt detekcji od 14 do 70°
- Obrót o 90° i pochylenie o 45° dla dogodnej instalacji
- Moduł czujnika jest ukryty
- Wysoka odporność na kurz i wilgoć (IP65)
- 5 lat gwarancji

6931P

Zewnętrzny czujnik ruchu, Dual Technology, 24 GHz

Specyfikacja techniczna

General

Technology	Dual
Application type	Wall mount
Anti masking	No
Pet immune	No
Camera	No

Detection

Max. detection range	15 m
Detection range	14 to 70° detection angle, 15 x 13 m
No. of curtains	21
Microwave frequency (nom.)	24 GHz
Undercrawl protection	No

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Alarm relay characteristic	NC, volt free relay, signal contact 24 VAC/DC @ 50 mA with an integral 25 Ohm series resistor

Electrical

Power supply value	10 to 15 VDC
Current consumption	8 mA (12 V nominal)

Physical

Physical dimensions	71 x 120 x 75 mm (W x H x D)
Net weight	225 g
Shipping weight	325 g
Colour	Bronze
Material	High impact ABS plastic with HDPE cover, UV stabilized
Mounting height	3 to 6 m

Environmental

Operating temperature	-30 to +65°C
Environment	Outdoor
IP rating	IP65

Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57