ATS1180M

Leitor de cartões MIFARE DESFire EV1/EV2/EV3 (Seguro) com saída e entrada RTE em design fino, preparado para soluções móveis.

Product overview

The ATS MIFARE DESFire EV1/EV2/EV3 readers connect directly to the control panel using the ATS databus. Communication to Advisor Advanced control panels is AES encrypted. In secure mode, card to reader data is also AES encrypted providing secure communication from the card to the processing unit. The readers are configured locally through keypad and control panel menu and the address is configures using the ATS1482 addressing card. Select secure cards from the ATS145x secure card series. The reader is also prepared to support future mobile credentials.
The reader offers a Request To Exit input and one open collector output that can be used to control a door relay or door strike.

The ATS118xM Mifare Desfire readers are designed to transfer card data in a secure and reliable way in various environments. The card data is by default secured by an Aritech own security key, but can be changed easily in Advisor Advanced control panels to any custom required key.
The readers can optionally be set to read MIFARE CSN numbers instead in unsecure mode.

Communication

The reader communicates in a secure way over the Advisor databus to Advisor control panels using AES encryption, securing the data from the card until being processed.

Design

The unique design of the housing guarantees that the reader can be used in the most demanding surroundings having IP67 and IK-09 rating. The reader can be installed directly on to a metal surface without any insulation.
Mounting brackets and weather protection covers provide extend the available applications.



Detalhes

- Leitor seguro ATS MIFARE DESFire EV1/EV2/EV3
- Preparado para credenciação móvel utilizando Bluetooth
- Suporta Mifare seguro (modo seguro) ou Mifare CSN/UID de 4 ou 7 bytes (modo não seguro)
- Utilizar cartões seguros da série ATS145x ou cartões de cliente
- Comunicação segura utilizando encriptação AES-128 bit entre o leitor e o painel de controlo Advisor Advanced / CDC4
- Caixa robusta em plástico moldado com design fino
- Instalação no interior ou no exterior
- Interface de Databus ATS
- Entrada de RTE
- Saída de coletor aberto (porta aberta)
- Suportado a partir do Advisor Advanced MR4.9
- NFC preparado para fins de configuração

ATS1180M

Leitor de cartões MIFARE DESFire EV1/EV2/EV3 (Seguro) com saída e entrada RTE em design fino, preparado para soluções móveis.

Especificações técnicas

System

Reading distance	Seguro: máx. 2 cm Não seguro: máx. 5 cm Bluetooth dependendo do dispositivo móvel e das definições
Max. reader distance to panel	1500 m
CSN (Card Serial Number)	Yes
Custom data model	Yes
Supported card types	MIFARE® Classic UID, MIFARE® DESFire UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Card Addressing
No. of LEDs	3
Language installation manual	Portuguese, Portugal

Technology

Reader type	Smart Card
Reader operating-transmitting frequency	13.56 MHz
Supported technology 13.56 MHz	MIFARE Classic (CSN), MIFARE DESFire (CSN), MIFARE DESFire EV1 (Aritech), MIFARE DESFire EV1 (CSN), MIFARE DESFire EV1 (custom data), MIFARE DESFire EV2 (Aritech), Mifare DESFire EV2 (CSN), Mifare DESFire EV2 (custom data), MIFARE DESFire EV3 (CSN), MIFARE DESFire EV3 (custom data)
Mifare type	ISO14443A
No. of Mifare bytes CSN	4 Bytes (non-unique), 4 Bytes (S50), 7 Bytes (S50), 7 Bytes (S70)

Interface & connections

Interface	ATS RS-485
Connector type	Pigtail
Pigtail length	2 m

Inputs/outputs

Inputs	Request to exit
Outputs	1 Open Collector (10 mA)

Tamper type

Pry-off tamper	Yes

Operation

Stand-alone	No
PIN keypad	No

Electrical

Operating voltage	10.8 a 30 VDC
Current consumption	55 mA @13.8 VDC normal 85 mA @13.8 VDC max.

Physical

Physical dimensions	140 x 44 x 20 mm
Net weight	240 g
Shipping weight	275 g
Colour	Black
Material	Plastic
Form factor	Slimline
Mounting Type	Surface mount

Environmental

Operating temperature	-40 a +55°C
Storage temperature	-40 a +55°C
Relative humidity	<95%, noncondensing
Environment	Indoor, Outdoor
IP rating	IP67 IK09

Regulatory

Compliancy	CE

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57