FRGO-55008

DTC4500e Base Model, USB and Ethernet Printer - Without Locking Hoppers, embedded Encoder, iCLASS SE, iCLASS, MIFARE/DESFire, and HID Prox Encoder (Omnikey 5127)



FRGO-55008

DTC4500e Base Model, USB and Ethernet Printer - Without Locking Hoppers, embedded Encoder, iCLASS SE, iCLASS, MIFARE/DESFire, and HID Prox Encoder (Omnikey 5127)

Tekniska specifikationer

General

Functionality	Printing
Encoding	HID MIFARE Classic, HID Prox, iCLASS, iCLASS SE, iCLASS Seos, iCLASS SR, MIFARE Classic, MIFARE DESFire EV1, SIO on MIFARE Classic, SIO on MIFARE DESFire EV1
Accepted standard card sizes	CR79, CR80
Supported operating system	Linux, Mac OS X, Windows 7, Windows 8.x, Windows Server 2003, Windows Server 2008, Windows Vista, Windows XP

Printing

Printing method	Direct To Card
Lamination	Single Sided
Printing side	Single Sided
Printer range	Fargo

Physical

Colour	Black

Regulatory

Compliancy	CE, RoHS

Kidde Global Solutions förbehåller sig rätten att ändra produktspecifikationer utan föregående meddelande. För de senaste produktspecifikationerna, besök se.firesecurityproducts.com online eller kontakta din försäljningsrepresentant.

Last updated on 12 November 2026 - 18:57