AS600FLASH

Flash module for AS 600 Series



Details

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- 300 x 210 x 87 mm
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Installer friendly
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

AS600FLASH

Flash module for AS 600 Series

Technical specifications

General

Accessory group	Sirene
Type	Ersatzteil

Flash specifications

Current consumption	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute

Electrical

Power supply value	10.5 to 13.8 VDC
Operating voltage	13 to 14.2 V
Current consumption	700 mA

Physical

Physical dimensions	300 x 210 x 87 mm
Net weight	3 kg
Material	Polycarbonat / Inox

Environmental

Operating temperature	-25 to 55°C

Sounder

Sound output at 1 m	110 dB
Frequency	0.7 to 1.2 kHz

Beacon

Spike suppression network	Standard fitted

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 21 January 2026 - 19:51