GS600

Minitec shock sensor

Mini inertia sensor

The GS600 is a miniature 4-wire inertia shock sensor. The GS600 can be mounted vertically or horizontally on any vertical structure such as walls, windows and doors. When the sensor is mounted in the vertical position, with the cable entering from below or above, the sensor is in its highest sensitivity position. When mounted horizontally, with the cable coming in from the side, the sensor is mounted in a damped position.

Easy installation

The GS600 is provided with a 2m 4-core cable, the blue and yellow wires are a tamper loop. The sensors are designed to be connected in series with the analysers GS614 or GS615.
The design of the sensor case allows the cable to enter through the back of the sensor housing, which enables a clean installation with no cable showing at the sensor head.

Performance

The good performance is achieved by means of precisely turned gold-plated rings with a gold-plated inertia mass placed through their centres, all resting on two precision made gold rails.
The GS600's unique design enables each ring to rotate independently. After each shock, a wiping action cleans the 16 contact points while at the same time retaining equal contact pressure. The sensor is hermetically sealed in an ABS plastic housing.



Details

- Reliable 24 hour loop perimeter protection
- Miniature attractive design
- Pre-wired 2m cable
- Suitable for all types of solid structures
- 24 carat gold plated internal mechanics for optimum performance & long life
- Two analysers available; GS614 & GS615

GS600
Minitec shock sensor

Technical specifications

General

Product type	Chok
Connections	4 wires, 2 m
LED identification	No

Wired/wireless

Wired-wireless	Kablede

Physical

Physical dimensions	17 x 14 x 42 mm (W x H x D)
Colour	Hvid

Environmental

Operating temperature	-40 to +50°C

Detection

Low sensitivity position	Vertically mounted
High sensitivity postion	Horizontally mounted

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:22