DD1012-N

12 m, dualna, 9 kurtyn, cyfrowy pyroelement

Patented range gated radar technology

Motion sensors of the DD1000 Series incorporate a KSG Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.
Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.
The radar operates on 5.8GHz frequency.

The DD1012-N motion sensor incorporates a new digital pyro for an improved signal quality and a better immunity to electrical interferences.

PIR technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.
Within our DD1012 series we are using a dual element pyro generating 2 volumetric curtains for each of the 9 curtain sets.

Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.
But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

Other members of the family

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity.
The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.



Szczegóły

- Opatentowana technologia radaru bramkującego zakresem z możliwością wyboru, wyraźnie określająca granicę wykrywania radaru
- Technologia PIR z opatentowaną optyką lustrzanej kurtyny
- Inteligentna decyzja alarmowa oparta na klasyfikacji sygnału alarmu PIR i radaru
- Automatyczna ciągła autodiagnostyka we wszystkich technologiach
- Tryb ECO: opcja wyłączenia technologii radarowej, gdy system bezpieczeństwa nie jest uzbrojony
- Holding several security approvals including EN Grade II
- Zawiera nowy cyfrowy pyro, który wykrywa wahania temperatury z dużą precyzją

DD1012-N

12 m, dualna, 9 kurtyn, cyfrowy pyroelement

Specyfikacja techniczna

General

Technology	Double
Application type	Fixation murale
Anti masking	No
Pet immune	No
Camera	No
Pry-off tamper kit	ST400
Detector start-up time	60 s

Detection

Max. detection range	12 m
Detection range selection	4, 6, 9, or 12 m selectable via dip switches
No. of curtains	9
Coverage (field of view)	78°
Microwave frequency (nom.)	5.8 GHz
Max. microwave output (at 1m)	0.003 µW/cm²
Undercrawl protection	Yes
Target speed range	0.2 to 3.0 m/s
Alarm memory	Yes
Alarm time	3 secondes
Peak-to-peak ripple immunity	2 V (at 12 VDC)

Wired/wireless

Wired-wireless	Wired

Inputs/outputs

Alarm relay characteristic	NC, 80 mA 30 VDC, Form A
Tamper relay characteristic	NC, 80 mA 30 VDC, Form A
Relay configuration	Valeurs EOL multiples
Remote control lines	Jour/Nuit, Test de fonctionnement

Electrical

Power supply value	9 to 15 VDC (12 V nominal)
Current consumption	5 to 16 mA (8 mA nominal)

Physical

Physical dimensions	126 x 63 x 50 mm
Net weight	120 g
Colour	Nuage blanc (RAL 9001)
Material	ABS
Mounting height	1.8 to 2.6 m

Environmental

Operating temperature	-10 to +55° C
Relative humidity	95% max. noncondensing
Environment	Indoor
IP rating	IP30 IK04

Regulatory

EN50131 grade	Grade 2
Compliancy	CE
Certification	INCERT, NFA2P, VdS



Będąc firmą innowacyjną, Kidde Global Solutions zastrzega sobie prawo do zmian w specyfikacji wyrobów bez uprzedzenia. W celu uzyskania najnowszych specyfikacji prosimy o wizytę na stronach pl/firesecurityproducts.com lub kontakt z przedstawicielem handlowym.

Last updated on 12 November 2026 - 18:57