# ATS1190X4

**4 pack ATS1190 Smart card reader with 2.5 m cable**



# ATS1190X4

## 4 pack ATS1190 Smart card reader with 2.5 m cable

## Spécifications techniques

### System

| | |
|---|---|
| Max. reader distance to panel | 1500 |
| Supported card types | HiTag2 |
| Addressing type | Indirizzamento tessere, Indirizzamento tastiere, Indirizzamento software |
| No. of LEDs | Tricolor |
| No. of covers included | 4, White |
| Reader accessory | Cover colorate opzionali |

### Technology

| | |
|---|---|
| Reader type | Nahdistanz, Smartcard |
| Reader operating-transmitting frequency | 125 KHz |
| Supported technology 125 kHz | HiTag 2 |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485, Wiegand |
| Connector type | Zopf |
| Pigtail length | 250 |

### Inputs/outputs

| | |
|---|---|
| Inputs | Richiesta di uscita |
| Outputs | 1 Open Collector (25 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| PIN keypad | No |

### Electrical

| | |
|---|---|
| Power supply value | 9 to 14 VDC |
| Current consumption | 80<br>25 |

### Physical

| | |
|---|---|
| Physical dimensions | 36 × 110 × 20 mm |
| Colour | Weiß |
| Material | Plastik |
| Mounting Type | Montaggio a superficie |

### Environmental

| | |
|---|---|
| Vandal proof | No |
| Operating temperature | -35 to +66 °C |
| Environment | Drinnen |
| IP rating | IP54 |

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57