# AB300

## Mid power beacon, white lens

### Operation

The range of low and high profile XENON beacons offers maximum light output and high efficiency for use in 10 to 15 V intruder alarms. Tested for IP65 rating, with polycarbonate lenses as standard, they are suitable for the most demanding applications.



### Details

- Maximum light output
- High efficiency
- Tested to IP65 rating
- Polycarbonate lens

# AB300

## Mid power beacon, white lens

## Technical specifications

### General

| | |
|---|---|
| Accessory group | Beacon |
| Type | Tilbehør |

### Flash specifications

| | |
|---|---|
| Light output | 0.9 nominal J |
| Flash frequency | 60 flashes/min |

### Electrical

| | |
|---|---|
| Power supply value | 10 to 15 VDC |
| Power consumption | 1 W |
| Operating voltage | 12 V |
| Current consumption | 115 mA |

### Physical

| | |
|---|---|
| Physical dimensions | 75 x 51 mm (Ø x H) |
| Colour | Hvid |

### Environmental

| | |
|---|---|
| Operating temperature | -30 to 70°C |
| IP rating | IP65 |

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 November 2025 - 12:40