POE304-EX-4P-V2

POE-bt to Gigabit Ethernet 4-port PoE+ Extender

Overview

The IFS POE304-EX-4P-V2 is remotely powered via Ethernet cable from a PoE-bt injecting device eliminating the need for local power requirements. The POE304-EX-4P-V2 can then transmit up to 4-ports of Ethernet data and PoE-af/at power dependent on the Powered Devices (PD) power demand.

The IFS PoE-bt solution facilitates easier network planning by eliminating restrictions of edge device placement near AC power outlets and reducing the need for AC wiring and installation costs.



Details

- 4-Port POE+ Switch powered by 1 x POE-bt input (up to 95W)
- Up to 75 watts shared POE power
- Plug-and-play self-powered design
- Can be used with an IFS PoE-Ultra Injector or other POE-bt compliant PSE equipment
- Supports 10/100/1000Base-T Ethernet
- Auto-detect of PoE equipment providing protection from incorrect installation
- Current overload detection
- LED Indicators for PoE In, PoE Out, Data
- Can be daisy-chained to extend data and PoE on a single network cable a maximum of 300m.

POE304-EX-4P-V2

POE-bt to Gigabit Ethernet 4-port PoE+ Extender

Technical specifications

General

Category	Przedłużacz PoE
Port type	10/100/1000
Port speed	Gigabit

Electrical

Power consumption	75 W

Physical

Physical dimensions	32 x 87 x 135 mm
Net weight	430 g

Environmental

Operating temperature	-40 to +75°C
Storage temperature	-40 to +85°C
Environment	Indendør
MTBF	>50,000 hrs. @ 25°C

Ethernet

Max Throughput (packet per second)	7.44Mpps at 64 Bytes
IEEE Standards	IEEE 802.3 Ethernet / IEEE 802.3u Fast Ethernet / IEEE 802.3ab Gigabit Ethernet
Latency	1765 ns (at 64 Byte Frame)
Maximum Frame Size	9 Kbytes
EIA/TIA-568 Standards	Category 5/5e cable

Power Over Ethernet (PoE)

PoE Standard	IEEE 802.3at
PoE Power Supply Type	POE-bt (No external power adaptor required)
PoE Output Pin Assignment	4/5(+), 7/8(-)
PoE Output Power with Multiple Extenders	4 x POE-af/at per port, 75 W max. shared power budget.

Connectors & Indicators

Ethernet + PoE In	1 x RJ-45 connector
Ethernet + PoE Out	4 x RJ-45 connector
LED Indicator	PWR (Green), PoE Power In (Mid-Span/End-Span - 2 x Green), PoE Power Meter (3 x Green), Input Port - LNC/ACT (Green) PoE (Amber), Per Port Output - LNC/ACT (Green) PoE (Amber)

Electrical & Mechanical

Input Power	Powered by POE-bt (PoE Switch or Mid-Span Injector)
Maximum Powered Devices	4
Enclosure	Metal
Power consumption	5 watts from PoE uplink

Standards Compliance

Regulatory	FCC Part 15 Class A, CE
EMI	EN 55022 CLASS A / EN61000-3-2 / EN61000-3-3
EMS	EN 55024 / IEC 61000-4-2 / IEC 61000-4-3 / IEC 61000-4-4 / IEC 61000-4-5 / IEC 61000-4-6 / IEC 61000-4-8 / IEC 61000-4-11 / IEC/EN 60950-1



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:25